



# Actinic BL TL(-K) / TL-D(-K)

## Actinic BL TL 6W/10 1FM/10X25CC

With an optimized spectrum matching the eye sensitivity of the housefly, Actinic BL TL(-K)/TL-D(-K)/TL-E/PL-S and PL-L lamps are perfect for attracting insects. They have virtually no UV-B output, and so are perfectly safe. What's more, with the lowest mercury content in the industry and being 100% lead-free, these lamps represent a very good environmental choice. Furthermore, the availability of a wide range of form factors (straight (T5, T8, T12), circular (TL-E) and compact (PL-S/PL-L)) and wattages enables you to make all kinds of designs for your electronic fly killers

### Product data

General Information	
Cap-Base	G5 [ G5]
Main Application	Insect traps
Life to 50% Failures (Nom)	10000 h
Useful Life (Nom)	5000 h

Light Technical	
Color Code	10
Color Designation	Actinic
Chromaticity Coordinate X (Nom)	222
Chromaticity Coordinate Y (Nom)	210
UV Depreciation at 500 h	17 %
UV Depreciation at 1000 h	25 %
UV Depreciation at 2000 h	35 %
UV Depreciation at 5000 h	50 %
UV Depreciation at 8000 h	60 %

Operating and Electrical	
Power (Nom)	6 W
Lamp Current (Nom)	0.16 A
Voltage (Nom)	42 V

Approval and Application	
Mercury (Hg) Content (Nom)	4.4 mg


UV	
UV-B/UV-A (IEC)	0.2 %
UV-A Radiation 100Hr (IEC)	1.4 W

Product Data	
Full product code	871150026039027
Order product name	Actinic BL TL 6W/10 1FM/10X25CC
EAN/UPC - Product	8711500260390
Order code	928000501030
Numerator - Quantity Per Pack	1

## Actinic BL TL(-K) / TL-D(-K)

Numerator - Packs per outer box	250
Material Nr. (12NC)	928000501030
Net Weight (Piece)	21.000 g

### Dimensional drawing



#### Product

Actinic BL TL 6W/10 1FM/10X25CC

TL 6W/10

### Photometric data

