PHILIPS Lighting

UV-B Narrowband TL

TL 40W/01 RS

More than 400 independent clinical studies have proven that the UVB Narrowband TL lamps are safer and more effective than any other lamps in their class. That is because these lamps emit only a very narrow waveband from the 'B' bandwidth of the UV spectrum (290 to 315). This narrow waveband is between 305 and 315 nm and peaks at 311 nm: the most efficacious waveband for the treatment of psoriasis. This means that treatment is much more focused and exposure times are much shorter. This in turn leads to a reduction of side effects such as reddening of the skin and itching. All of this makes them ideal for phototherapy treatment of diseases such as psoriasis and vitiligo. What's more, because the overall dosage of this narrowband radiation can be closely controlled, these lamps are suitable for home therapy.N.B.: Our UVB lamps are NOT registered with FDA as medical devices as they are NOT packaged or labeled for commercial distribution for health-related purposes. US customers are referred to the UVB and UVA lamp range brochure US version.

Product data

General Information	
Cap-Base	G13 [Medium Bi-Pin Fluorescent]
Main Application	Medical Therapy
Life to 50% Failures (Nom)	9000 h
Useful Life (Nom)	9000 h
System Description	Rapid Start
Light Technical	
Color Code	01
Color Designation	Ultra Violet B
Chromaticity Coordinate X (Nom)	208
Chromaticity Coordinate Y (Nom)	192
UV Depreciation at 500 h	10 %

UV Depreciation at 1000 h	15 %		
Operating and Electrical			
Power (Rated) (Nom)	39 W		
Lamp Current (Nom)	0.43 A		
Voltage (Nom)	104 V		
UV			
UV-B Radiation 100 hr (IEC)	7.5 W		
UV-B Radiation 5hr (IEC)	7.7 W		
Product Data			
Full product code	871869666239700		
Order product name	TL 40W/01 RS		

UV-B Narrowband TL

EAN/UPC - Product	8718696662397	Material Nr. (12NC)	928011300130
Order code	928011300130	Net Weight (Piece)	292.000 g
Numerator - Quantity Per Pack	1		
Numerator - Packs per outer box	25		

Warnings and Safety

• A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Dimensional drawing

TL 40W/01 RS

s 100

80

60

40 20

200

Lightcolor /01

300

400

500


600

700

lnm

Photometric data

Product	D (max)	A (max)	B (max)	B (min)	C (max)
TL 40W/01 RS	40.5 mm	1199.4 mm	1206.5 mm	1204.1 mm	1213.6 mm



⁵ 100 80 60 40 20 200 300 400 500 600 700 λ [nm]

Lightcolor /01

PHI	LIPS
Æ	
E	
	Ŧ

© 2018 Philips Lighting Holding B.V. All rights reserved. Philips Lighting reserves the right to make changes in specifications

and/or to discontinue any product at any timewithout notice or obligation and will not be liable for any consequences resulting from the use of this publication.

www.lighting.philips.com 2018, July 19 - data subject to change